

OPUS C 220-19.2 C

OPUS C series DC Power
System in Cabinet



General description

OPUS C 220-19.2 C delivers uninterrupted DC power to demanding industrial, automation, telecom and datacom applications. Maximum output power is 19.2 kW at 220 VDC.

OPUS C 220-19.2 C is a compactly integrated DC power system using MRC 220-1600 convection cooled rectifiers and a comprehensive VIDDI controller. Connections are preinstalled for mains, batteries and DC distribution. The system can be equipped with a wide range of options.

Features

- Fully integrated 220 VDC power system
- All-inclusive distribution with load fuse monitoring
- Options: temperature compensated charging, load LVD, battery LVD, comprehensive battery management, relay inputs and outputs, remote control, overvoltage protection and earth fault detection
- Can be supplemented with inverters
- Floor-mounted cabinet in several sizes
- Also available in 24 VDC, 48 VDC, 60 VDC and 110 VDC versions

Technical specifications

General construction	
Cooling	Natural convection
Protection	IP 20
Controller user interface	Display and local control in front door
Distribution and Connections	Inside cabinet, cabling from top (from bottom on request)
Rectifiers	Max. 12 pcs
Material	1-1.5 mm zinc plated steel cabinet and door
Color	Cabinet RAL 7037, door RAL 7035
Assembly	Standalone floor-mounted cabinet

Input	
AC-connection	3W+N+PE
Nominal voltage	230/400 VAC
Range, full power	180-275 VAC
Range, reduced power	140-180 VAC
Frequency	45 to 65 Hz
Nominal current / phase	2 x 15.2 A
Maximum current / phase	2 x 19.4 A
Inrush current	17 A / rectifier
Rectifier input protection	16 A MCB / rectifier module
Mains terminal	Terminal blocks 10 mm ²
Recommended external mains fuse	2 x (3x25)
Mains switch	2 x 40 A

Output	
Nominal voltage	220 VDC
Voltage range	189-265 VDC
Overvoltage shut-down	270 VDC
Ripple noise	<100 mV _{p-p}
Nominal current	86.4 A@220 V
Output current	78 A@245.3 V
Nominal power max.	19.2 kW
Redundant power	17.6 kW
Output terminals	max. 25 mm ²

Battery connection	
MCCB	1 pc 4P 63 A

Controller	
VIDI	Basic controller
VIDI+	Advanced controller
Features	See VIDI datasheet

Load distribution options (monitored)	
MCB	1-30 pcs/2-pole
NH 00 fuse link	1-15 pcs/2-pole
Rating of load fuses	MCB 2...50 A/NH 00 6...125 A

Other options	
Second battery MCCB	4P 63 A
Temperature sensor	Enables temperature compensated charging
Transient OVP	Available for input protection
Inverters	Supplementary OPUS inverters

Dimensions	
Height mm	2000
Width mm	600
Depth mm	600
Weight without rectifiers kg	

Environment and standards	
Operating temperature	-5°C - +45°C
Humidity max.	95% relative humidity, non-condensed
Altitude max.	2000 m above sea level
Safety	IEC/EN 60950-1
EMC	Emissions: EN/ IEC 61000-6-4 Immunity: EN/ IEC 61000-6-2 Harmonic currents: EN/ IEC 61000-3-2 Voltage fluctuations& flicker: EN/ IEC 61000-3-3